

SPIN 15 & SPIN 30 PLUS

CONTINUOUS MIXER FOR PREMIXED MATERIALS

INDUSTRY CHANGING, HIGH-OUTPUT CONTINUOUS MIXERS

Ideal for quickly and efficiently mixing; preblended plasters, mortars, stuccos, grouts, self-leveling underlayments, preblended conventional floor-screeds. Team the continuous mixer with an IMER spray and grout pump for semi-automatic production.




WATER FLOW METER

Allows the water level to be set for easy setup when using the same material.



WATER PUMP

Standard on the Spin 30 and optional on the Spin 15. Used to boost the water flow or siphon from a tank.



Technical specifications

	SPIN 15A	SPIN 30 PLUS
Model #	1106340	1106152
Hopper / tank capacity	250 lbs	500 lbs
Mixing performance	.5 cu ft / min	1 cu ft / min
Mixer/paddle speed	280 rpm	280 rpm
Motor power rate	1.75 hp	3 hp (220v single-phase)
Standard power rate	optional	yes
Standard dust grate	yes	yes
Weight (with packaging)	187 lbs (196 lbs)	281 lbs (292 lbs)
Dimensions w/l/h	27.5" x 54" x 46"	25" x 71" x 46"
Box dimensions	31.5" x 23.25" x 32.5"	N/A

